



Kaypro

SURFACE MOUNTED & SUSPENDED | TEC EM SERIES

The Kaypro product family is a set of modular luminaires designed especially for modern office environments and retail spaces, with dropped ceilings. Highly modular, easy to install and maintain. Simple and compact design that supplies the maximum visual comfort. Comes in standard ceiling dimensions of 60x60 cm, 62x62 cm and 120x30 cm. It has three mounting options: recessed, surface mounted (60 x 60 cm; 120 x 30 cm) or suspended.

The Kaypro SM Family has several series, determined by various add-on and controls:


- Kaypro SM TEC – the standard for office spaces
- Kaypro SM TEC EM – with emergency lighting kit
- Kaypro SM ECO-DALI – with DALI controls for illumination adjustments
- Kaypro SM ECO-DALI EM - with both dimming and emergency kit

Features & Benefits

- CRI 80 as standard
- 4 color temperatures: 3000K, 4000K, 5000K, 6500K
- Long rated life: L90/B10@50,000h
- Luminaire efficiency: 110 lm/W @4000K
- UGR: 18-19

Applications & References

Office | Healthcare | Hospitality | DIY




Specifications

Power consumption	32W, 38W, 50W	
Dimensions	595 x 595 x 58 ± 1mm	1195 x 295 x 58 ± 1mm
Weight	6.3 - 6.4Kg	6.3 - 6.4Kg
Housing materials	Steel sheet & Polycarbonate	
IK code	IK04	
THD (at 230V, 50Hz, Full load)	<8%	
Protection class	Safety class 1	
Operating temperature [°C]	+5C...+45C/+41F...+113F	
Operating humidity [%]	10 ÷ 85	
Power factor	≥0.95	
AC Input [Vac]	220 - 240 VAC	
Lens angle [°]	100°	
Lifespan [h]	50,000	
Housing color	○ RAL 9003 - Signal white	
Lumen maintenance	L90/B10@50.000h at 25°C	
IP factor	IP20	
Control optional	For product information please see Kaypro SM ECO-DALI EM datasheet	
Warranty [years]	5	
Storage temperature range [°C]	+5C...+25C/+41F...+77F	
Emergency option	EM1H, EM3H	

Light application	Standard
CRI	CRI 80
CCT [K]	3000K/4000K/5000K/6500K
MacAdam	4

CRI - Color rendering, CCT - Color temperature, MacAdam - Color consistency

Light distribution



A110

RISK GROUP**RG1**

The evaluation of photobiological safety is carried out according to the standard IEC 62471:2008 ("Photobiological safety of lamps and lamp systems"). Following the definition of the risk grouping system of the mentioned IEC standard, the LEDs mounted on this family fall into the class "Low Risk (RG1 – No photobiological hazard under normal behavioral limitations)". Under real circumstances (regarding exposure time, pupils, observation distance), it is assumed that there is no endangerment to the eye from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect.

TOLERANCES

Luminous flux tolerances: -/+ 5%

Consumption tolerance: -/+ 5% for TEC | -/+ 10% for TEC & KIT EM | -/+ 10% for ECO-DALI | -/+ 15% for ECO-DALI & KIT EM

BATTERY WARRANTY

TEC EM & ECO EM: 12 months warranty

TEC & ECO: -

MAXIMUM NO. OF LUMINAIRES ON A CIRCUIT

Power	Driver type	Control type	Circuit Breaker Type						
			Amperage	B			C		
				20	16	10	20	16	10
< 50W		TEC		37	30	18	62	51	31
≥ 50W		TEC		37	30	18	62	51	31
< 80W		ECO		27	21	13	45	35	21

SKU SPECIFICATIONS

Product Code	Dimensions (mm)	CCT (K)	Lumens (lm)	Power (W)	Eff. (lm/watt)	Lens Angle (°)
CRI 80						
111072 Kaypro 2L 6060/SM/3000/32W/80/EM1H	595 x 595 x 58 ± 1mm	3000	3350	32W	105	100°
111073 Kaypro 2L 6060/SM/4000/32W/80/EM1H	595 x 595 x 58 ± 1mm	4000	3490	32W	110	100°
111074 Kaypro 2L 6060/SM/5000/32W/80/EM1H	595 x 595 x 58 ± 1mm	5000	3585	32W	113	100°
111075 Kaypro 2L 6060/SM/6500/32W/80/EM1H	595 x 595 x 58 ± 1mm	6500	3490	32W	110	100°
111076 Kaypro 2L 6060/SM/3000/38W/80/EM1H	595 x 595 x 58 ± 1mm	3000	3940	38W	104	100°
111077 Kaypro 2L 6060/SM/4000/38W/80/EM1H	595 x 595 x 58 ± 1mm	4000	4105	38W	109	100°
111078 Kaypro 2L 6060/SM/5000/38W/80/EM1H	595 x 595 x 58 ± 1mm	5000	4215	38W	111	100°
111079 Kaypro 2L 6060/SM/6500/38W/80/EM1H	595 x 595 x 58 ± 1mm	6500	4105	38W	109	100°
111080 Kaypro 2L 6060/SM/3000/50W/80/EM1H	595 x 595 x 58 ± 1mm	3000	4825	50W	97	100°
111081 Kaypro 2L 6060/SM/4000/50W/80/EM1H	595 x 595 x 58 ± 1mm	4000	5030	50W	101	100°
111082 Kaypro 2L 6060/SM/5000/50W/80/EM1H	595 x 595 x 58 ± 1mm	5000	5165	50W	104	100°
111083 Kaypro 2L 6060/SM/6500/50W/80/EM1H	595 x 595 x 58 ± 1mm	6500	5030	50W	101	100°
111144 Kaypro 2L 6060/SM/3000/32W/80/EM3H	595 x 595 x 58 ± 1mm	3000	3350	32W	105	100°
111145 Kaypro 2L 6060/SM/4000/32W/80/EM3H	595 x 595 x 58 ± 1mm	4000	3490	32W	110	100°
111146 Kaypro 2L 6060/SM/5000/32W/80/EM3H	595 x 595 x 58 ± 1mm	5000	3585	32W	113	100°
111147 Kaypro 2L 6060/SM/6500/32W/80/EM3H	595 x 595 x 58 ± 1mm	6500	3490	32W	110	100°
111148 Kaypro 2L 6060/SM/3000/38W/80/EM3H	595 x 595 x 58 ± 1mm	3000	3940	38W	104	100°
111149 Kaypro 2L 6060/SM/4000/38W/80/EM3H	595 x 595 x 58 ± 1mm	4000	4105	38W	109	100°
111150 Kaypro 2L 6060/SM/5000/38W/80/EM3H	595 x 595 x 58 ± 1mm	5000	4215	38W	111	100°
111151 Kaypro 2L 6060/SM/6500/38W/80/EM3H	595 x 595 x 58 ± 1mm	6500	4105	38W	109	100°
111152 Kaypro 2L 6060/SM/3000/50W/80/EM3H	595 x 595 x 58 ± 1mm	3000	4825	50W	97	100°
111153 Kaypro 2L 6060/SM/4000/50W/80/EM3H	595 x 595 x 58 ± 1mm	4000	5030	50W	101	100°
111154 Kaypro 2L 6060/SM/5000/50W/80/EM3H	595 x 595 x 58 ± 1mm	5000	5165	50W	104	100°
111155 Kaypro 2L 6060/SM/6500/50W/80/EM3H	595 x 595 x 58 ± 1mm	6500	5030	50W	101	100°
111096 Kaypro 1L 12030/SM/3000/32W/80/EM1H	1195 x 295 x 58 ± 1mm	3000	3350	32W	105	100°
111097 Kaypro 1L 12030/SM/4000/32W/80/EM1H	1195 x 295 x 58 ± 1mm	4000	3490	32W	110	100°
111098 Kaypro 1L 12030/SM/5000/32W/80/EM1H	1195 x 295 x 58 ± 1mm	5000	3585	32W	113	100°
111099 Kaypro 1L 12030/SM/6500/32W/80/EM1H	1195 x 295 x 58 ± 1mm	6500	3490	32W	110	100°
111100 Kaypro 1L 12030/SM/3000/38W/80/EM1H	1195 x 295 x 58 ± 1mm	3000	3940	38W	104	100°
111101 Kaypro 1L 12030/SM/4000/38W/80/EM1H	1195 x 295 x 58 ± 1mm	4000	4105	38W	109	100°
111102 Kaypro 1L 12030/SM/5000/38W/80/EM1H	1195 x 295 x 58 ± 1mm	5000	4215	38W	111	100°
111103 Kaypro 1L 12030/SM/6500/38W/80/EM1H	1195 x 295 x 58 ± 1mm	6500	4105	38W	109	100°
111104 Kaypro 1L 12030/SM/3000/50W/80/EM1H	1195 x 295 x 58 ± 1mm	3000	4825	50W	97	100°
111105 Kaypro 1L 12030/SM/4000/50W/80/EM1H	1195 x 295 x 58 ± 1mm	4000	5030	50W	101	100°
111106 Kaypro 1L 12030/SM/5000/50W/80/EM1H	1195 x 295 x 58 ± 1mm	5000	5165	50W	104	100°
111107 Kaypro 1L 12030/SM/6500/50W/80/EM1H	1195 x 295 x 58 ± 1mm	6500	5030	50W	101	100°
111168 Kaypro 1L 12030/SM/3000/32W/80/EM3H	1195 x 295 x 58 ± 1mm	3000	3350	32W	105	100°
111169 Kaypro 1L 12030/SM/4000/32W/80/EM3H	1195 x 295 x 58 ± 1mm	4000	3490	32W	110	100°
111170 Kaypro 1L 12030/SM/5000/32W/80/EM3H	1195 x 295 x 58 ± 1mm	5000	3585	32W	113	100°
111171 Kaypro 1L 12030/SM/6500/32W/80/EM3H	1195 x 295 x 58 ± 1mm	6500	3490	32W	110	100°
111172 Kaypro 1L 12030/SM/3000/38W/80/EM3H	1195 x 295 x 58 ± 1mm	3000	3940	38W	104	100°
111173 Kaypro 1L 12030/SM/4000/38W/80/EM3H	1195 x 295 x 58 ± 1mm	4000	4105	38W	109	100°
111174 Kaypro 1L 12030/SM/5000/38W/80/EM3H	1195 x 295 x 58 ± 1mm	5000	4215	38W	111	100°
111175 Kaypro 1L 12030/SM/6500/38W/80/EM3H	1195 x 295 x 58 ± 1mm	6500	4105	38W	109	100°
111176 Kaypro 1L 12030/SM/3000/50W/80/EM3H	1195 x 295 x 58 ± 1mm	3000	4825	50W	97	100°
111177 Kaypro 1L 12030/SM/4000/50W/80/EM3H	1195 x 295 x 58 ± 1mm	4000	5030	50W	101	100°
111178 Kaypro 1L 12030/SM/5000/50W/80/EM3H	1195 x 295 x 58 ± 1mm	5000	5165	50W	104	100°
111179 Kaypro 1L 12030/SM/6500/50W/80/EM3H	1195 x 295 x 58 ± 1mm	6500	5030	50W	101	100°

Technical specifications can be modified without prior notice. All information is property of Greentek Lighting.

The presentation picture is for information purposes only. Latest document update: November 6, 2017 6:40 PM. www.greentek.eu